

Technical Bulletin



| Model(s) | Year | Eng. Code | Trans. Code | VIN Range From | VIN Range To |
|-----------------------------------|---------------------|--|-------------|----------------|--------------|
| All with TDI-PD Touareg TDI-PD | 2004 – 2006 2004 | BEW 1.9 TDI BHW 2.0 TDI BRM 1.9 TDI BKW 5.0 TDI | All | All | All |

Condition

17 07 06 Mar. 7, 2007 2010419 supersedes Technical Bulletin Group 17, number 05-05 due to inclusion in ElsaWeb and additional models.

Engine Oil, Volkswagen Oil Quality Standard VW 505 01 Requirement

Technical Background

The TDI-PD (Pumpe-Düse) engine requires, and must always use, engine oil that conforms to Volkswagen Oil Quality Standard VW 505 01.

Production Solution

N / A

Service



WARNING

Failure to use engine oil for your engine that expressly conforms to Volkswagen Oil Quality Standard VW 505 01 can cause engine failure on the highway that can cause a crash and serious personal injury.

Whether you use a synthetic-based or petroleum-based* engine oil, the oil must conform to Volkswagen Oil Quality Standard VW 505 01 in order to keep the engine running smoothly, and to help prevent the formation of harmful sludge and deposits that can lead to expensive repairs.

* At this time, all of the engine oils of which Volkswagen is aware that meet the exacting Volkswagen Oil Quality Standard VW 505 01 are synthetic-based.

For a list of approved engine oils, refer to Volkswagen Technical Bulletin Instance 2012855.

The list is also available at www.vw.com and at www.vw.ca.

Technical Bulletin



Engine oil, servicing

All scheduled Volkswagen services and topping off of engine oil between services require engine oil that meets Volkswagen Oil Quality Standard VW 505 01.

No other engine oil may be used in this engine unless it conforms to the Volkswagen Oil Quality Standard VW 505 01.

Engine oil, topping off

It is recommended that the customer always carry a spare liter or quart of oil that meets Volkswagen Oil Quality Standard VW 505 01, in case the engine oil needs to be topped off while on the road. The spare liter or quart of oil should always be stored in its original container, securely closed, and stowed in the luggage compartment.

Engine damage caused by the use of the wrong engine oil will not be covered by the respective Vehicle Warranty.

Warranty

Information only

Required Parts and Tools

No special parts are required.

No special tools are required.