

KVW100 Auto Window Module

Vehicle Application List:

For All 1J0 959 799AJ convenience modules			For All 1C0 959 799C convenience modules		
1998-2001	New Beetle		2002-2006	Golf	
2000-2001	Golf		2002-2005	Jetta	
1999-2001	Jetta		2002-2006	Jetta Wagon**	
1998-2001	Passat		2001-2005	Passat	

** This product will modify the hatch lock function of the Jetta Wagon. Pressing the hatch FOB button will now "pop" open the hatch similar to the trunk of the Jetta Sedan.

Installation Instructions

For all vehicles

1. First find your **OBD-II interface plug** located beneath the steering wheel under the dash.
2. Put your key into the ignition and turn the **ignition switch to "ON"**, there is no need to start the vehicle.
3. Plug the **KVW100** into your OBD-II interface plug. Make sure it is a snug fit. The KVW100 will give a **single long beep**, once it is fitted properly.

The update time is about 2 minutes. If the KVW100 gives 3 short beeps then congratulations! Your car has been updated successfully!

It now has the functions of Auto Windows

4. After the update, pull the KVW100 out from the OBD-II interface plug.

Note:

If the KVW100 gives **continuous short beeps**, then the update failed. You must pull it out, wait a few seconds, and then plug it into the OBD-II interface plug again. You can try up to 6 times. If it still fails, please contact our distributor directly: <http://www.szkw.com/english/distributors.htm>

Operation Instructions

Convenience Module 1C0 959 799C or 6Q0 959 799C

Action	Result
One touch of the "lock" button	Windows and Sunroof roll up and close automatically
"lock +lock" (press quickly)	Windows and Sunroof keep their original position
Hold on the "unlock" button	Windows will roll down while "unlock" button is held
Release hold of "unlock" button	Windows will stop rolling down

Convenience Module 1JO 959 799AJ

Action	Result
Hold on the "lock" button	Windows and Sunroof roll up and close while holding button
Hold on the "unlock" button	Windows will roll down while "unlock" button is held
Release hold of "unlock" button	Windows will stop rolling down

Adding New Key FOB's

For Convenience Module 1C0 959 799C Only

If you add a new key FOB you will lose the "One touch" roll up feature. You can still perform the hold "lock" button roll up.

You can restore the new key FOB for the "One touch" roll-up feature with the following steps:

1. Put your key into the ignition and turn the ignition switch to "ON", there is no need to start the vehicle
2. Plug the KVV100 into your OBD-II interface plug. Make sure it is a snug fit. The KVV100 will give a single long beep, once it is fitted properly
3. When the green led light on the KVV100 is on, hold the driver's door "lock" button
4. When you hear a long beep from the KVV100 again, release the door "lock" button
5. Wait for 2 minutes you will hear kvw100 give 3 short beep then pull it out