

90 hp engine

Engine data

Maximum output SAE net	90 hp at 3750 rpm
Maximum torque SAE net	155 ft. lbs. at 1900 rpm (210 Nm at 1900 rpm)
No. of cylinders	4
Displacement	115.7 CID (1.896 cm ³)
Stroke	3.75 in (95.5 mm)
Bore	3.13 in (79.5 mm)
Compression ratio	19.5 : 1
Fuel ¹⁾	Diesel

Capacities

Fuel tank	<i>in gal. / liters</i>	14.5 / 55
Reserve (included in total capacity)	<i>in gal. / liters</i>	1.9 / 7.0
Windshield washer container	<i>in quarts. / liters</i>	3.2 / 3.0
Engine oil ¹⁾	<i>in quarts. / liters</i>	4.8 / 4.5

Maximum Permissible Trailer Weights ²⁾		Automatic transmission	Manual transmission
Trailer without brakes	<i>in lbs. / kg</i>	1000 / 454	1000 / 454
Trailer with brakes	<i>in lbs. / kg</i>	1000 / 454	1000 / 454
Tongue load	<i>in lbs. / kg</i>	165 / 75	165 / 75

¹⁾ The engine oil level should be checked while topping up.

Do not overfill - see "Engine oil," chapter "CHECKING AND FILLING" **Booklet 3.2.**

²⁾ See also "Trailer towing," chapter "DRIVING AND PROTECTING OUR ENVIRONMENT" **Booklet 3.2.**

Note

The spark ignition system meets all requirements of the Canadian Interference-Causing Equipment Regulations.