



Product Information Sheet

Material Safety Data Sheet (MSDS) also available



Product : XHD SAE 5W-40

Part # : 29500, 29503

Type : Engine Oil

Engine : Diesel

Description: Synthetic Heavy Duty Diesel Engine Oil

Fleet tested at 160,000 km* intervals

* Environmental conditions and driving patterns may affect oil longevity. Periodic sampling recommended after first 45,000 km

Revision # 1

Problem / Symptom

XHD 5W-40 was developed for today's modern diesel engines, equipped with EGR valves in highway tractors, off-road diesel powered equipment and diesel powered passenger vehicles.

Performance

- ☞ Formulated to protect against viscosity and thermal breakdown
- ☞ It's high 11.5 TBN combined with its greater oxidation stability promote extended oil drains
- ☞ Specifically designed for running with high or low sulphur diesel fuels
- ☞ Excellent low temperature vicometrics (-45°C) provide improved year-round fuel economy
- ☞ **160,000 km** Fleet Oil, with periodic oil sampling after 45,000 km.

Application

Refer to owner's manual for engine specifications and fill capacities.

Characteristics

Will meet or exceed the following performance requirements

- ☞ API SL, CF, CG-4, CH-4, CI-4, PC-9
- ☞ ACEA E5-99 & MB228.3
- ☞ Global DHD-1
- ☞ Cummings 200076-77-79
- ☞ Ford, Navistar, GM, John Deere, Caterpillar & Detroit Diesel
- ☞ Mack OE-M, OE-M Plus & OE-M Premium Plus
- ☞ Volvo VDS-2 & VDS-3

Packaging

1L	12 bottles per case	84 cases per skid	25 Lbs. / Case
4 L	6 bottles per case	50 cases per skid	35 Lbs. / Case
205 L	Drum	4 drums per skid	435 Lbs. / Drum